

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) Air separator system for separating shredded trash into pieces of relatively light material and relatively heavy material, comprising:
 - a first conveyor system having a conveyor belt wrapping around a roller at one end of the conveyor belt, the conveyor belt having a direction of travel to the roller at the one end, and conveying the pieces shredded trash, in the direction of travel, to the end of the conveyor belt;
 - an air manifold positioned directly underneath and approximately at the end of the conveyor belt for blowing the pieces of shredded trash as they exit the end of the conveyor belt with an air stream which is generally in the direction of travel of the conveyor belt to the roller at one end;
 - a splitter plate system disposed at a position forward of the end of the conveyor system comprising a rotatable cylinder which is essentially parallel to the roller at the end of the conveyor belt;
 - means for adjusting the speed and direction of rotation of the rotatable cylinder;and
 - means for moving the splitter plate system towards and away from the first conveyor system.
2. Cancelled
3. (previously presented) Air separator system, according to claim 1, wherein:
 - the roller rotates in a counterclockwise direction; and
 - the cylinder is rotated in the same direction.
4. (previously presented) Air separator system, according to claim 3, further comprising:

a splitter sheet hanging below the cylinder, defining a first accumulation area on one side of the splitter sheet which is proximal the first conveyor system; and

a second accumulation area on another side of the splitter sheet which is distal the first conveyor system.

5. (previously presented) Air separator system, according to claim 4, wherein:

the second accumulation area has a second conveyor system for removing the lighter materials that accumulate on the side of the splitter sheet which is distal the first conveyor system.

6. (Original) Air separator system, according to claim 1, wherein:

the conveyor belt is disposed at an angle "a" with respect to horizontal; and
the angle is approximately 30-60 degrees.

7. (Currently Amended) A splitter plate system for use in conjunction with a conveyor system for separating shredded trash into pieces of relatively light material and relatively heavy material, comprising:

the conveyor system having a conveyor belt with a direction of travel for conveying the pieces shredded trash in the direction of travel;

an air manifold positioned at the end of the conveyor belt for blowing the pieces of shredded trash as they exit the end of the conveyor belt with an air stream which is generally in the direction of travel;

a structural frame having two side elongate elements and a bottom rotatable cylinder extending between the side elongate elements disposed at a position forward of the end of the conveyor system;

means for adjusting the speed and direction of rotation of the rotatable cylinder;

a splitter sheet hanging from the two side elongate elements; and

means for moving the structural frame towards and away from the conveyor system.

8. Cancelled

9. (Original) A splitter plate system, according to claim 7, including:

means for raising and lowering the structural frame.

10. Cancelled

11. (Original) A splitter plate system, according to claim 7, wherein:

the structural frame is a generally rectangular structural frame having a top elongate element and two opposite side elongate elements extending downwards from opposite ends of the top elongate element, and a bottom elongate element extending between bottom portions of the side elongate elements, thereby forming a generally rectangular window; and

the splitter sheet hangs from bottom ends of the two side elongate elements.

12. (currently amended) Method of separating pieces of shredded trash into relatively light material and relatively heavy material, comprising the steps of:

conveying the pieces of shredded trash, in a direction of travel, to an end of a conveyor having a roller at one end;

blowing the pieces of shredded trash as they exit from the end of the conveyor with an airstream blown from a air manifold positioned directly underneath and approximately at the end of the conveyor belt which is generally in the direction of travel of the conveyor;

disposing a a splitter plate system, including a rotatable cylinder which is essentially parallel to the roller at the end of the conveyor and a splitter sheet, forward of the end of the conveyor;

adjusting the speed and direction of rotation of the rotatable cylinder;

rotating the rotatable cylinder; and

moving the splitter plate system with respect to the first conveyor system so that the relatively lighter pieces of material will be projected over the rotatable cylinder for collecting the relatively heavier pieces of material in a first accumulation area on one side of the splitter sheet which is proximal the end of the conveyor and collecting the relatively lighter pieces of material in a second accumulation area on an opposite side of the splitter sheet which is distal the end of

the conveyor.

13. cancelled

14. (previously presented) Method, according to claim 12, further comprising the steps of:
- controlling an amount of pieces which are collected in the second accumulation area by
 - adjusting at least one of the following parameters:
 - a speed of the conveyor,
 - an angle of the conveyor with respect to horizontal,
 - an angle of the airstream with respect to the angle of the conveyor,
 - a pressure of the airstream,
 - a position of the airstream relative to the end of the conveyor,
 - a distance between the cylinder and the conveyor, and
 - a height of the cylinder with respect to a height of the conveyor.